

## MATERIAL SAFETY DATA SHEET

### 1 - Preparation and company identification

Identification of the preparation Oil Vacuum Pump 007935090600  
 Preparation use Lubricant for compressors, hydraulic systems and vacuum pumps.  
 Company ELKE S.A.S. di Amosso Domenico & C.  
 Via G. Deledda 72 - 10060 Candiolo (Torino) -Italy-  
 (Tel.+39 011-9622412)

Emergency telephone Poisons Department, Niguarda Hospital, Milan -Italy-  
 Tel. +39 02 66101029

Business references mail: domenico.amosso@elke-ac.com

### 2 - Hazards identification

Information None

Hazards The substance is not regarded as hazardous according to the Directive 1999/45/EEC.

Main risks to health/environment No particular risks in normal working conditions of the product. We recommend, however, to keep normal personal hygiene and to avoid frequent contacts and over an extended period of time. Use according to good working practice avoiding to dispel the product in the environment.

### 3 - Composition / Information on ingredients

Ingredients composition	Dithiophosphoric acid esters	<0,17 %	N R51/53
	Hyndered alkylphenol	<0,22 %	R53
	Alkylated diphenylamines	<0,35 %	R52/53
	Derivate of phosphorothioic acid esters	<0,08 %	R53
	Sulfur containing sterically hindered phenol	<0,09 %	R53
	Please refer to section 16 for more information about R phrases referred to.		

Components information The content of DMSO extract, determined with the IP 346/92 method is lower than 3% in weight.

Chemical composition Paraffinic base stocks blended with additive packages.

### 4 - First aid measures

First aid measures are necessary for the preparation use

Inhalation In case of exposure to high concentration of oil mist, move into fresh air. Seek medical attention if necessary. If you suspect that there has been inhalation, urgently go to hospital with the patient.

Contact with the eyes Immediately flush eyes with large amounts of water and keep eyelids open for a few minutes. Get prompt medical attention.

Contact with the skin Remove contaminated clothing. Wash thoroughly with water and then with soap and water. If symptoms persist, seek medical attention.

Ingestion Do not induce vomit to avoid sucking through the respiratory tract. Seek medical help.

**MATERIAL SAFETY DATA SHEET**

---

**5 - Fire-fighting measures**

Fire-fighting equipment	Extinguish flames with foam, dry chemicals, CO <sub>2</sub> .
Inappropriate extinguishers	Do not use direct water jets. Use water jets just to cool down surfaces exposed to fire.
Specific dangers in case of exposition to the chemicals, its combustion products or gases	Avoid breathing combustion fumes that, in case of fire, can form carbon monoxide fuel gases, carbon dioxide, sulphur, phosphorus, nitrogen and unburnt hydrocarbon compounds and other derivatives potentially dangerous.
Specific protective equipment for fire-fighting personnel	Wear protective overalls with self-breathing equipment.

**6 - Accidental release measures**

Person - related safety precautions	Wear gloves and protective glasses. In case of spillage of considerable quantities into bordering place, avoid to breathe exhalations; air the environment or wear protective breathing apparatus. Remove any possible ignition sources.
Environmental precautions	The product contains substances harmful to the aquatic environment. Avoid to drain the product into sewers or into waterways otherwise inform the relevant local authorities.
Decontamination procedures	In case of significant amount of spilled product, control and transfer the product in suitable containers. Spillage on ground: Control spilled product with earth or sand. Clean up spilled product and dispose according to local regulations. Spillage in water: Border immediately the spillage. Remove spilled product from the surface with mechanical equipment.

**7 - Handling and storage**

Handling	Avoid direct contacts with the product. Do not breathe aerosol or product vapours guaranteeing a suitable ventilation in working areas.
Storage	Keep the product in original containers. Storage in a fresh place, away from heating sources and direct sun exposition. Avoid to accumulate electrostatic charge. Keep closed and covered the containers to avoid infiltrations of rain. Maintain suitable ventilation of the work place.
Empty containers	The containers contain product residues. Dispose the containers in safe ecological way according to the local regulations.

**8 - Exposure controls / personal protection**

According to data in our possession, any component presents exposure limits in working place.

Breathing equipment	Not necessary under normal working conditions. Keep oil hazes within the TLV-TWA limit of 5 mg/m <sup>3</sup> . (A.G.C.I.H. 2000). Use masks with filters for organic vapours in case of exposure superior to the fixed limits.
Hands and skin protection	Wear gloves and protective overalls; change immediately contaminated clothes and wash them thoroughly before use. We recommend to keep normal personal hygiene and of working clothes. Wear gloves only after having thoroughly washed your hands.
Eyes protection	Wear safety protective glasses where it is possible to be in contact with the product.
Exposure control	Avoid the formation of hazes or aerosol and use ventilation or localized aspiration if necessary.

**MATERIAL SAFETY DATA SHEET**

---

**9 - Physical and chemical properties**

Physical status :	Liquid
Odour :	Typical
pH :	Not applicable
Water Solubility :	Insoluble
Density at 15°Ckg/l :	0,890
Kinematic Viscosity at 40°CcSt :	68
Flash Point (C.O.C.)°C :	220
Pour Point°C :	-9

**10 - Stability and reactivity**

Reactivity	Avoid contacts with strong acid, strong bases and oxidation agents. Avoid extreme heat and high energy sources of ignition.
Stability	Stable product in normal applications.

**11 - Toxicological information**

Oral toxicity	LD50 (rats): > 2000 mg/kg (estimated). The product if ingested can irritate the digestive apparatus and induce vomiting, cause nausea and diarrhea.
Skin contact	LD50 skin (rabbit) > 2000 mg/kg (estimated). Frequent and continuous contacts could degrease skin and cause dermatitis.
Eyes contact	It can cause light irritation.
Inhalation	Long term exposure to the product mist can cause irritation to the respiratory system.
Chronic toxicity	Exposure to oil vapour that exceeds Professional Inhalation Limits can cause respiratory system irritations.

**12 - Ecological information**

Mobility	The product keeps afloat.
Persistence and	Not determined.
Accumulation	Not determined.
Ecotoxicity	In compliance with EEC Regulations the product is not regarded as hazardous to the environment.

**13 - Disposal considerations**

General information	Do not dispel the environment. Comply with the current laws.
Disposal	Discharge the exhausted products and the containers through the authorized industries in compliance with the state and local regulations for disposal of this type of waste.

**14 - Transport information****Not hazardous for the transport.**

Transport name	Oil Vacuum Pump	007935090600
----------------	-----------------	--------------

**15 - Regulatory information**

Hazard symbols	None
R Phrases	

**MATERIAL SAFETY DATA SHEET**

---

None

S Phrases

None

**16 - Other information**

Relevant R Phrases

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R53 May cause long-term adverse effects in the aquatic environment.

Warning

The information presented in this Material Safety Sheet is based on data believed to be accurate as of the date this Material Safety Data Sheet was prepared. The purpose of this data sheet is to inform and assume a correct technological use of the product. ELKE S.A.S. does not take any responsibility resulting from any damage or injury resulting from abnormal use.

Reference laws

This Safety Data Sheet complies with the Regulation 1999/45/EEC, 2006/8/EEC and is in compliance with the regulations (EEC) 1907/2006 (REACH).