

## SAFETY DATA SHEET

Page: 1/3

Revised edition no: 1 Date: 12/2/2008

Supersedes: 0/0/0

# 5% Hydrogen in Nitrogen

0264

#### 1 IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING

: 5% Hydrogen in Nitrogen Trade name : Air Liquide UK Ltd. Company identification

Station Road Coleshill

Birmingham B46 1JY United Kingdom

: 01675 462695 **Emergency phone nr** 

#### **2 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substance / Preparation** : Preparation.

Components : This product is not hazardous but contains hazardous components.

#### 3 HAZARDS IDENTIFICATION

**Hazards identification** : In high concentrations may cause asphyxiation.

Compressed gas.

#### **4 FIRST AID MEASURES**

First aid measures

- Inhalation : In high concentrations may cause asphyxiation. Symptoms may include loss of

mobility/consciousness. Victim may not be aware of asphyxiation.

Remove victim to uncontaminated area wearing self contained breathing

apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if

breathing stopped.

: Ingestion is not considered a potential route of exposure. - Ingestion

## **5 FIRE-FIGHTING MEASURES**

Flammable class : Non flammable.

Specific hazards : Exposure to fire may cause containers to rupture/explode.

**Hazardous combustion products** 

**Extinguishing media** 

- Suitable extinguishing media : All known extinguishants can be used.

Specific methods : If possible, stop flow of product.

Move away from the container and cool with water from a protected position.

Special protective equipment for fire : In confined space use self-contained breathing apparatus.

#### **6 ACCIDENTAL RELEASE MEASURES**

Personal precautions : Evacuate area.

Ensure adequate air ventilation.

Wear self-contained breathing apparatus when entering area unless atmosphere is

proved to be safe.

**Environmental precautions** : Try to stop release. Clean up methods : Ventilate area.

Air Liquide UK Ltd.

In case of emergency: 01675 462695



# **SAFETY DATA SHEET**

Page: 2/3

Revised edition no : 1

Date : 12 / 2 / 2008

Supersedes: 0/0/0

# 5% Hydrogen in Nitrogen

0264

#### 7 HANDLING AND STORAGE

Storage : Keep container below 50°C in a well ventilated place.

**Handling** : Open valve slowly to avoid pressure shock.

Suck back of water into the container must be prevented.

Do not allow backfeed into the container.

Use only properly specified equipment which is suitable for this product, its supply

pressure and temperature. Contact your gas supplier if in doubt.

Refer to supplier's container handling instructions.

#### 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection : Ensure adequate ventilation.

#### 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state at 20 °C : Compressed gas.

Colour : Colourless.

Odour : Odourless.

Relative density, gas (air=1) : Lighter or similar to air.

Solubility in water [mg/l] : No reliable data available.

#### 10 STABILITY AND REACTIVITY

Stability and reactivity : Stable under normal conditions.

### 11 TOXICOLOGICAL INFORMATION

**Toxicity information** : No known toxicological effects from this product.

#### 12 ECOLOGICAL INFORMATION

**Ecological effects information** : No known ecological damage caused by this product.

Effect on ozone layer : None.

#### 13 DISPOSAL CONSIDERATIONS

General : Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

**Disposal method** : Consult supplier for specific recommendations.

#### 14 TRANSPORT INFORMATION

**UN No.** : 1956 **H.l. nr** : 20

ADR/RID

Proper shipping name : COMPRESSED GAS, N.O.S. (Nitrogen, Hydrogen)

- ADR Class : 2 - ADR/RID Classification code : 1 A

**Labelling ADR** : Label 2.2 : Non flammable, non toxic gas.

Other transport information : Avoid transport on vehicles where the load space is not separated from the driver's



# **SAFETY DATA SHEET**

Page: 3 / 3

Revised edition no : 1
Date : 12 / 2 / 2008

Supersedes: 0/0/0

# 5% Hydrogen in Nitrogen

0264

### 14 TRANSPORT INFORMATION (continued)

compartment

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.
- Ensure there is adequate ventilation.
- Compliance with applicable regulations.

### 15 REGULATORY INFORMATION

**EC Labelling** : Not classified as dangerous preparation/substance.

Symbol(s): None.R Phrase(s): None.S Phrase(s): None.

## **16 OTHER INFORMATION**

**Training advice** : Asphyxiant in high concentrations.

Keep container in a well-ventilated place.

Do not breathe the gas.

The hazard of asphyxiation is often overlooked and must be stressed during

operator training.

Receptacle under pressure.

Ensure all national/local regulations are observed.

End of document